



Bus Model:	KLQ6675GEV (6.7 METER) two step
------------	---------------------------------

Standard seat number :		23+1 (2x2 seats)	Wheelbase	mm	3450
Overall dimensions:	mm	6750x2340x3110	Max speed	km/h	70
Approach/Departure Angle		10/11	Kerb mass	kg	6300
Overhang front / rear	mm	1720/1580			

STANDARD CHASSIS	
Batter Capacity	127 kWh CATL lithium iron phosphate battery
Driver Motor	Higer Motor
Charging Type/Port	GB (China standard)
Suspension	AIR SUSPENSION
ABS	WABCO ABS
Axle	Fangsheng front axle/Fangsheng rear axle (disk braking) Independent front axle
Braking system	Pneumatic dual circuit full air brake, storage energy spring braking.
Tire:	215/75R17.5 tubelss tire

STANDARD BODY	
A/C :	NTC Aircon,
Passenger Seats:	Passenger seat with safety belts
Driver Seat:	Pneumatic adjustable
Windows:	Push-pull side window; push-pull driver's window
Automobile data recorder:	With
Passenger Door:	Pneumatic inward-swing door
Rear view mirror:	With
Audio-visual	With standard player; reverse camera
Others:	Interior Ceiling Lamp; 1pc roof exit; safety hammers; Spare tire; In-car video surveillance; Fire Extinguisher in battery compartment; USB; 10 rings; Driver fan